

4/9/16 Channel, Triplex, Networkable, Stand-alone DVR

	<u>EST4120</u>	<u>EST9120</u>	<u>EST16120</u>	<u>EST16240</u>	<u>EST16480</u>
Camera Input	4 ch	9 ch	16 ch	16 ch	16 ch
Audio Input	4 ch	4 ch	4 ch	4 ch	4 ch
Sensor / Control	4 / 1	9 / 9	16 / 16	16 / 16	16 / 16
Display Speed	120 fps	270 fps	480 fps	480 fps	480 fps
Recording Speed	120 fps	120 fps	120 fps	240 fps	480 fps
Video Output	TV & VGA	TV & VGA & S-Video			
Loop-Back Output	-	9 ch	16 ch	16 ch	16 ch
Multi-screen Display	1, 4	1, 4, 9, PIP	1, 4, 9, 16, PIP		
Compression	MPEG-4 Yielding Average 2Kbytes per Frame at 360x240				
Recording Resolution	360x240, 720x240, 720x480				
Recording Mode	Continuous, Motion, Sensor, Pre/Post, Schedule				
Playback Search	Date & Time, Camera, Event Search				
External Interface	RS232C, RS485, RJ45(Ethernet), USB				
Camera PTZ Control	RS-422/485 Interface				
Network Interface	LAN & WAN (Support DHCP, static and dynamic IP)				
Network Functions	Live View, Search, Setup, PTZF control				
Camera Setup	Receiver Type, PTZF, Audio, Sensor, Auto Switching Interval				
Motion Detection	Setup Areas Per Each Camera				
Notification	Email in Emergency				
Password Protection	Support Admin with Passwords				
OS Platform	Real-time OS (RT-OS)				
Internal HDDs Support	1	4			
Backup File Format	JPEG, AVI				
Backup Support	USB, External CD-RW, External DVD-RW				
Remote Features	Monitoring, Playback, Setup, Backup Scheduling, Camera Control, PTZ, Upgrade				
Total Management	Central Monitoring System – Multiple Site Connections Simultaneously				

Entel America (www.entelamerica.com)
info@entelamerica.com
 187 W. Orangethorpe Ave, Suite B
 Placentia, CA 92870
 (714) 528-1656